



Paydar Saz Shimi

Paydar Saz Shimi
#٨٠٤, Yaran Tower, Kashani Blvd.,
Tehran, 14818 7554⁹-Iran
Tel: +98 (21) 4407 7150-1
Fax: +98 (21) 4407 7471
Website: www.pschemi.com

Payastab™ KZ 2424L

Product Description:

Payastab™ KZ 2424L is a medium-fast kicker with good heat stability and excellent initial color which imparts excellent microcellular foam structure combined with a smooth surface. The incorporation 2-5 phr **Payaflex™ ESO-65** gives an optimum performance.

Applications:

Payastab™ KZ 2424L is specially designed for flexible PVC foam articles.

Typical Properties:

Assay	Units	TYPICAL VALUES	METHODS
Appearance	==	Liquid	Visual
Colour (Gardner)	==	7.0	ASTM D1544
Density @ 25°C	g/cm ³	0.98± 0.02	ASTM D5355
Refractive Index @ 25°C	==	1.451	ASTM D1218 - 02
Viscosity @ 25°C	cP	18.0	ASTM D5125

Recommended dosage:

Depends on the formulation, processing conditions and the type of product; the quantities ratio to the blowing agent may vary from 3:1 to 1:3.

Information for safe handling:

Open and handle receptacle with care.

Storage:

Cap should be kept closed. Store in a cool location; store in dry condition.

Standard Packaging:

200 Kg barrel, conform to the UN regulation

DISCLAIMER: To the best of our knowledge the information stated here is correct. All products may present unknown health hazards and should be used with caution. Final determination of suitability is the sole responsibility of the user. Users of the products should satisfied themselves that the conditions and methods of use assure that the product is used safely. No representation or warranties either express or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to information contained herein or the product to which the information refers. Nothing herein is intended as a recommendation to use our products so as to infringe any patent. We assume no liability for customer's violation of patent or rights.