

Paydar Saz Shimi

Paydar Saz Shimi #^••, Yaran Tower, Kashani Blvd., Tehran, 14818 75549-Iran Tel: +98 (21) 4407 7150-1 Fax: +98 (21) 4407 7471

Website: www.pschemi.com

VinylostabTM CZ 55

Product Description:

VinylostabTM CZ 55 is a non-toxic Liquid Ca/Zn stabilizer. It imparts Good initial color, good transparency and long-term heat stability. The addition of Υ phr Payaflex 65, due to its synergistic effect, prevents zinc burn and leads to higher heat stability.

Applications:

Vinylostab™ CZ 55 is used in all type of processing especially extrusion and injection molding of plasticized PVC especially for non-toxic applications. It may also be used in plastisol processing.

Typical Properties:

Assay	Units	TYPICAL VALUES	METHODS
Appearance	<u> </u>	Liquid	Visual
Colour	==	white	Visual
Density @ Y7ºC	g/cm3	٠,٩٦٠	ASTM D5355
Viscisity @ 25°C	cP		ASTM D5125

Recommended dosage:

Depends on the formulation, processing conditions and the type of product; usually in the range of 1.5-3 phr.

Information for safe handling:

Open and handle receptacle with care.

Storage:

Cap should be kept closed. Store in a cool and dry location.

Standard Packaging:

200 Kg barrel, conform to the UN regulation

DISCLAIMER: To the best of our knowledge the information stated here is correct. All products may present unknown health hazards and should be used with caution. Final determination of suitability is the sole responsibility of the user. Users of the products should satisfied themselves that the conditions and methods of use assure that the product is used safely. No representation or warranties either express or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to information contained herein or the product to which the information refers. Nothing herein is intended as a recommendation to use our products so as to infringe any patent. We assume no liability for customer's violation of patent or rights.